



RONER TOUCH

80012 RONER TOUCH

The new Roner Touch combines the renewed design of the Roner with the digital technology of the touch screen, to which it adds a series of features that make it a unique model on the market.

Technical data

- Temperature range: from room temperature to 200°C
- Water pump flow rate: 15 l/min
- Temperature stability: + - 0.1°C
- Optimised operation at 50 litres with thermal bath.
- Power W: 2060
- Timer: Up to 99h 59min
- Automatic disconnection due to low liquid level.
- New fan protection and improved pump.
- Minimum depth for fixing to the tray: 14 cm.
- Voltage: 230 V / 50-60Hz.



Functions

- Audible and visual alarm.
- Calendar clock.
- Simple or cyclical on/off programming.
- Up to 10 work programmes.
- Memorisation of alarms and incidents.
- Probe error detection.
- Detection and memorisation of mains failures.
- Over-temperature and under-temperature alarms and their memorisation (date, start time, end time and temperature).
- Safety thermostat (TS) by software.
- Mechanical safety thermostat (TS).
- USB output, R-232.
- Configurable parameters: Date/time, temperature correction, data collection interval, language (English, Spanish and French), °C/°F selection.
- Over-temperature and under-temperature limit.

Format

Package measurements : 35 x 24 x 25 cms

Weight: 5 Kgs.

Customs code: 9032.10.20

EAN: 8436537860084

